





ALUMINIUM DISPLAY



Ip65 Front Panel



Accessible power button



Wide temperature range



Wide range power input

MODEL	BASIC-116	
I/O		
VGA	1	
HDMI	-	
DVI	1	
DP	1	
TOUCHSCREEN	USB	
OTHERS	USB Front Panel	
POWER	4-pin DC terminal block; 2-pin remote power switch	
DISPLAY		
DISPLAY TYPE	15.6" TFT-LCD 16:9	
MAX RESOLUTION	1366 x 768	1920 x 1080
MAX COLOR	16.7 M	
BRIGHTNESS (cd/m²)	300	
VIEW ANGLE (H°/V°)	160/160°	
CONTRAST	500:1	
TOUCHSCREEN		
TYPE	Resistive Zero Bezel (R)	
INTERFACE	USB	
POWER		
POWER INPUT	9 ~ 36V DC	
POWER CONSUMPTION	12.2W MAX	
MECHANICAL		
CONSTRUCTION	Aluminium front panel	
IP RATING	IP66 front panel	
MOUNTING	Panel Mount/VESA Mount 100x100	
DIMENSIONS (mm)	451 x 300 x 59	
NET WEIGHT (kg)	4.4 kg	
ENVIRONMENT		
OPERATING TEMPERATURE	0 ~ 50° C	
STORAGE TEMPERATURE	-20 ~ 70° C	
STORAGE UMIDITY	10 ~ 90% @40 non-condensing	
CERTIFICATION	CE	
ORDERING		
BASIC-116	15.6" TFT, 1366x768, RST, 9-36V DC, 500cd/m2	
BASIC-116F	15.6" TFT, 1920x1080, RST, 9-36V DC, 500cd/m2	

