


## ALUMINIUM PANEL PC

MECHANICAL	
CONSTRUCTION	Aluminium Front Bezel
MOUNTING	Panel Mount
DIMENSIONS (mm)	451 x 300 x 82
NET WEIGHT (kg)	7 kg
IP RATING	IP65 compliant front bezel
CERTIFICATE	CE / FCC Class A
ENVIRONMENT	
OPERATING TEMPERATURE	0 ~ 50° C
STORAGE TEMPERATURE	-20 ~ 70° C
STORAGE HUMIDITY	10 ~ 90 % non-condensing
INQUIRY CODES	
BASIC-916-FN8	15.6" TFT 16:9, 1366x768, 8th Gen. Intel® Core, RST, 9-36V DC, 300cd/m²
BASIC-916F-FN8	15.6" TFT 16:9, 1920x1080, 8th Gen. Intel® Core, RST, 9-36V DC, 300cd/m²
NOTE	RAM and Storage capacity must be specified in the inquiry

MODEL	BASIC-916-FN8	
SYSTEM		
CPU	8th Gen. Intel® Core™ (Whiskey Lake-U), 15W i3-8145UE, DC, 2.2GHz   i5-8365UE, QC, 1.6GHz   i7-8665UE, QC, 1.7GHz	
SYSTEM CHIPSET	MCP	
MEMORY	2x 260-pin SO-DIMM, Dual Channel DDR4 2400MHz, max. 32GB	
OPERATING SYSTEM	Windows 10/11®	
GRAPHICS	Intel® Graphics DX 12	
INTERFACE PORTS		
LAN	2x RJ45 GbE LAN (1x Intel® i219V, 1x Intel® i210AT) with 10/100/1000 Mbps	
SERIAL	3x RS232, 1x RS232/422/485	
USB	4x USB 3.2 (Gen2), 2x USB 3.2 (Gen1), 2x USB 2.0	
VIDEO	2x DP 1.2, 1x LVDS	
GPIO	4x GPI + 4x GPO	
AUDIO	2x Audio (Mic-In, Line-Out), 1x Speaker Header	
STORAGE		
M.2	1x Key M (2242/2280) with PCIe x4 and SATA3 for SSD 1x Key M (2242) with SATA3 for SSD	
SATA	1x SATA3 (6Gb/s)	
RAID	Supports Intel® SATA RAID 0/1	
EXPANSIONS		
M.2	1x Key E (2230) with PCIe x1, CNVI and USB 2.0 for Wireless	
DISPLAY		
DISPLAY TYPE	15.6" TFT-LCD 16:9	
MAX RESOLUTION	1366 x 768	1920 x 1080 (F)
MAX COLOR	16.7M	
BRIGHTNESS (cd/m²)	300	
VIEW ANGLE (H°/V°)	85/80	
CONTRAST	1000:1	
TOUCHSCREEN		
TYPE	Resistive (R)	
INTERFACE	USB	
LIGHT TRANSMISSION	Resistive: 80	
POWER		
POWER INPUT	9 ~ 36V DC	
POWER CONSUMPTION	MAX. 60W	
POWER PORTS	1x 3-pin DC power input terminal, 1x 2-pin connector for ON/OFF button	



404 CUTOUT

290

252 CUTOUT

199.8

