



COMPACT



| Model Name | COMPACT-K715-S6 |
|---------------------------------|---|
| System | |
| CPU | Intel® Core™ i7 / i5 / i3 / Celeron™ (Skylake-S) Processors |
| System Chipset | Intel H110 |
| System Memory | 2x SO-DIMM 32GB DDR4 2133MHz |
| I/O | |
| Interface | 4x USB 3.0, 1x HDMI, 1x DP, 2x Audio (Mic-in, Line-out), 1x VGA, 2x COM (1x RS232, 1x RS232/422/485), 2x RJ45 GbE LAN (1x Intel I219V, 1x Intel I210) |
| Storage Space | |
| SATA | SATA3 (6.0Gb/s), 1x mSATA, 2x SATA (one SATA shared with mSATA) |
| Expansion | |
| Expansion Slot | 1x PCIe x16, 1x Mini-PCIe (half/full-size, supports PCIe x1 & USB device) |
| Display | |
| Display Type | 15" TFT-LCD 4:3 |
| Max. Resolution | 1024 x 768 |
| Max. Color | 16.7M |
| Luminance (cd/m ²) | 500 |
| View angle (H°/V°) | 85 / 85 |
| Contrast | 1500 : 1 |
| Touch Screen | |
| Type | 5 wire Resistive |
| Interface | USB |
| Light transmission (%) | Resistive: 80% |
| Power | |
| Power Input | 110 ~ 230V AC - 47/63Hz |
| Power Consumption | 270W |
| Mechanical | |
| Construction | Aluminum Front Bezel |
| IP rating | IP65 Front Bezel |
| Mounting | Panel mount |
| Dimension (mm) | 483 x 399 x 98.5 |
| Net Weight (Kg) | 7.5 |
| Environment | |
| Operating Temperature | 0 ~ 50°C |
| Storage Temperature | -20 ~ 70°C |
| Storage Humidity | 10 ~ 90% @40 non-condensing |
| Operating System Support | |
| Windows® | Windows® 10 (64bit) / 8.1 (64bit) / 8 (64bit) / 7 (64bit) |

