



STAINLESS STEEL PANEL

MECHANICAL	
CONSTRUCTION	Flat Front Bezel Design, 304 Stainless Steel chassis
MOUNTING	VESA Mount 100x100, Yoke Mount (Option)
DIMENSIONS (mm)	571 x 362 x 55
NET WEIGHT (kg)	10 kg
IP RATING	IP66/IP69K compliant front bezel
CERTIFICATE	CE / FCC Class A
ENVIRONMENT	
OPERATING TEMPERATURE	0 ~ 50° C
STORAGE TEMPERATURE	-30 ~ 70° C
STORAGE HUMIDITY	10 ~ 95% @40 non-condensing
INQUIRY CODES	
CiNOX-821R	21.5" TFT, 1920x1080, Intel® Celeron N2930, RTS, 9-36V DC, 250cd/m2
CiNOX-821RH	21.5" TFT, 1920x1080, Intel® Celeron N2930, RTS, 9-36V DC, 1000cd/m2
CiNOX-821P	21.5" TFT, 1920x1080, Intel® Celeron N2930, PCT, 9-36V DC, 250cd/m2
CiNOX-821PH	21.5" TFT, 1920x1080, Intel® Celeron N2930, PCT, 9-36V DC, 1000cd/m2

MODEL	CiNOX-821	
SYSTEM		
CPU	Intel® Celeron™ N2930, 1.83GHz, 2M Cache	
SYSTEM CHIPSET	SoC	
MEMORY (MAX)	On board 4GB DDRL3 SDRAM, up to 8GB (option)	
OPERATING SYSTEM	Windows 10®	
GRAPHICS	Intel HD® Graphics 313/854MHz	
INTERFACE PORTS		
USB/SERIAL	1x M12 8-pin for USB 2.0 with waterproof cover and chain	
	1x M12 8-pin COM1, RS-232/422/485, default RS-232	
LAN	1x M12 8-pin for LAN with waterproof cover and chain	
ADDITIONAL PORTS	2x Optional blank M12 for selecting two of the following option:	
	2x USB 2.0 1x USB 3.0	
	1x LAN (POE for option)	
	1x COM 1x CAN	
STORAGE		
HDD	1x 2.5" SATA3 HDD	
EXPANSIONS		
EXPANSION SLOT	1x Full-size Mini-PCIe socket (PCIe + USB) for WiFi/BT/LTE (optional)	
	RFID module design on the front side (optional)	
DISPLAY		
DISPLAY TYPE	21.5" TFT-LCD 16:9	
MAX RESOLUTION	1920 x 1080	
MAX COLOR	16.7M	
BRIGHTNESS (cd/m²)	250	1000
VIEW ANGLE (H°/V°)	170/160	
CONTRAST	1000:1	1000:1
TOUCHSCREEN		
TYPE	Resistive (R)	Projected Capacitive (P)
INTERFACE	USB	
LIGHT TRANSMISSION	Resistive 80%	Capacitive 90%
POWER		
POWER INPUT	9 ~ 36V DC	
POWER CONSUMPTION	MAX. 30W	
POWER PORTS	1x M12 3-pin for DC power with waterproof cover and chain	
	1x Power switch on the rear	

