


ALUMINIUM DISPLAY




Ultra Narrow Frame



Special Fasteners



Removable Cover



New Mounting

MODEL	HELIO-110	
I/O		
VGA	1	
DP	1	
HDMI	1	
AUDIO	1 (Line-in)	
OTHERS	1x USB type A for Touch, 1x RS-232 Db9 for Touch (optional)	
OSD CONTROL MEMBRANE	5 Keys at rear	
POWER	1x 3-pin Terminal Block Connector	
DISPLAY		
DISPLAY TYPE	10.1" TFT-LCD 16:10	
MAX RESOLUTION	1280 x 800	
MAX COLOR	16.7M	16.2M
BRIGHTNESS (cd/m ²)	350	1000
VIEW ANGLE (H°/V°)	170/170	
CONTRAST	800:1	1300:1
TOUCHSCREEN		
TYPE	Projected Capacitive (P)	
INTERFACE	USB	
LIGHT TRANSMISSION	Capacitive: 90	
POWER		
POWER INPUT	9 ~ 36V DC	
POWER CONSUMPTION	5.28W	
MECHANICAL		
CONSTRUCTION	Aluminium die-casting chassis	
IP RATING	IP66 Compliant Front Bezel	
MOUNTING	Panel/VESA Mount 100 x 100	
DIMENSIONS (mm)	269 x 189 x 51	
NET WEIGHT (kg)	1.6	
ENVIRONMENT		
OPERATING TEMPERATURE	0 ~ 50° C	
STORAGE TEMPERATURE	-30 ~ 70° C	
STORAGE HUMIDITY	10 ~ 90% @40, non-condensing	
CERTIFICATE	CE/FCC, Class A	
ORDERING		
HELIO-110P	10.1" TFT, 1280x800, PCT, IP66, 9-36V, 350cd/m ²	
HELIO-110PH	10.1" TFT, 1280x800, PCT, IP66, 9-36V, 1000cd/m ²	

