



MODEL	HST-010C
<b>SYSTEM</b>	
CPU	MSM8953 OCTA Core
CPU SPEED	2.0GHz
GPU	ADRENO 506
OPERATING SYSTEM	Android 10
RAM	4GB LPDDR3
ROM	64GB EMMC
<b>DISPLAY</b>	
DISPLAY TYPE	10.1" 16:10
MAX RESOLUTION	1920x1200
TOUCH SYSTEM	Multipoints G+G capacitive 7H
BRIGHTNESS (cd/m <sup>2</sup> )	400
<b>I/O</b>	
INTERFACE	1x HDMI 1.4a, 1x USB 3.0 Type A, 1x USB Type C, 1x SIM, 1x TF, 1x DB9 RS232, 1X RJ45, 1x 12pins pogo pin
AUDIO	1x Ø3.5mm standard earphone jack, 1x speaker 8Ω/0.7W
CONTROL BUTTONS	ON/OFF, vol +/-, F Key, P1, P2
<b>CAMERA</b>	
FRONT	5.0MP
REAR	13.0MP with Flash and auto-focus
<b>POWER INPUT</b>	
BATTERY	Removable, Li_polymer, 10000mAh/3.7V
ENDURANCE	12hrs (50% volume, 200 lumens, video display 1080P by default)
ADAPTER	AC 100V ~ 240V, 50/60Hz, Output DC 5V/3A
<b>MECHANICS</b>	
DIMENSIONS	280 x 187 x 22 mm
WEIGHT	1.014 Kg
<b>ENVIROMENTAL FEATURES</b>	
PROTECTION DEGREE	IP65
CERTIFICATIONS	CE NB / FCC / RoHS
	MIL-STD-810G 1.22M drop
	Battery UN38.3, MSDS, IEC62133
OPERATING TEMPERATURE	-20° ~ +55°C
STORAGE TEMPERATURE	-30° ~ +70°C
HUMIDITY	5% ~ 95% non-condensing

## INDUSTRIAL RUGGED TABLET

### APPLICATION MODULES

WIRELESS	WiFi 802.11 b/g/n/a/ac 2.4G+5G dual band
BLUETOOTH	BT4.1 BLE
SENSORS	1x Light, 1x Gravity Acceleration sensor
NFC	NFC NXP 13.56MHz ISO/IEC 1443A/14443B/15693/18092/mifare, Identification Distance 4cm
2G / 3G / 4G	CMCC 4M_ LTE B1,B3,B5,B7,B8,B20,B38,B39,B40,B41; WCDMA 1/2/5/8; GSM 2/3/5/8
GPS	Supports GPS 1575.42MHz / Glonass 1602MHz
1D BARCODE READER (Optional)	MOTOSE655E100R Optical resolution 5mil; Scan speed 50/s; Code System: UPC/EAN, Bookland EAN, UCC, ISSN EAN, Code 128, GS1-128, ISBT 128, Code 39, Trioptic Code 39/21/93/11
2D BARCODE READER (Optional)	<b>EM80</b> ; Optical resolution 5mil; Scan speed: 50times/s; Code System: PDF417, MicroPDF417, Data Matrix/Inverse Maxicode, QR, MicroQR, QR Inverse, Atztec/Inverses; Han Xin/Inverse

### ACCESSORIES

Optional	Docking Charger, Vehicle Docking, Hand Strap, Car Holder, Battery, Power Adapters
----------	---

## HST-010C



## ACCESSORIES

