



INDUSTRIAL RUGGED TABLET

APPLICATION MODULES	
WIRELESS	WiFi 802.11 b/g/n/ac 2.4G+5.8G Dual Band
BLUETOOTH	Bluetooth 5.0
SENSORS	1x Gravity Acceleration sensor
NFC (Optional)	Supports ISO/IEC 14443A/B, ISO/IEC 15693, ISO/IEC 18092, ISO/IEC mifare protocol
4G (Optional)	LTE FDD: B1/B3/B7/B8/B20 LTE-TDD: B40
	WCDMA: B1/B5/B8 GSM: B3/B8
GPS	Built-in, GPS, Glonass
2D BARCODE READER (Optional)	MOTOSE4710 ; Optical resolution 5mil; Scan speed: 50/s; Code System: PDF417, MicroPDF417, Data Matrix/Inverse Maxicode, QR, MicroQR, QR Inverse, Atztec/Inverses; Han Xin/Inverse
ACCESSORIES	
Optional	Docking charger, Vehicle Mounting Docking, Straps, Power Adapters

MODEL	HST-408
SYSTEM	
CPU	Intel® Celeron® N5100
CPU SPEED	2.8 GHz
GPU	Intel® HD Graphics
OPERATING SYSTEM	Windows® 10 / Windows® 10 PRO (Optional)
RAM	4GB LPDDR3 Optional 8GB
ROM	64GB Optional 128GB
DISPLAY	
DISPLAY TYPE	8" 16:10 TFT LCD
MAX RESOLUTION	1920x1200
TOUCH SYSTEM	5 points G+G capacitive 7H
BRIGHTNESS (cd/m²)	550
I/O	
INTERFACE	1x USB 3.0 Type A, 1x USB Type C, 1x SIM, 1x TF, 1x HDMI 1.4a
AUDIO	1x Φ3.5mm standard earphone jack
CONTROL BUTTONS	ON/OFF, vol +/-, Home, Custom Key
CAMERA	
FRONT	5.0MP
REAR	8.0MP
POWER INPUT	
BATTERY	Li_polymer, 5000mAh / 7.6V - removable
ENDURANCE	6hrs (default 50% volume, 200 lumens, video display by default)
ADAPTER	AC 100V ~ 240V, 50/60Hz, Output DC 19V/3.42A
MECHANICS	
DIMENSIONS	236.7 x 155.7 x 20 mm
WEIGHT	0.910 Kg
ENVIROMENTAL FEATURES	
PROTECTION DEGREE	IP65
CERTIFICATIONS	CE NB
	MIL-STD-810G 1.22m drop
	UN38.3, MSDS, IEC62133
OPERATING TEMPERATURE	-20° ~ +55°C
STORAGE TEMPERATURE	-30° ~ +70°C
HUMIDITY	5% ~ 95% non-condensing



ACCESSORIES



Holding Straps



Car Charger



Vehicle Docking



Docking Station