


## ALUMINIUM PANEL PC



Fanless Design



IP65 Front Panel



DC 12V/19V/24V/36V



Projected Capacitive 10 point

MODEL	LIGHT-816A
<b>SYSTEM</b>	
CPU	RK3568 Quad-core Cortex up to 2.0GHz
SYSTEM CHIPSET	Mali-G52 GPU
MEMORY (MAX)	Onboard 2GB, Optional 4GB
STORAGE	16GB, Optional 32GB
OPERATING SYSTEM	Android® 11
<b>INTERFACE PORTS</b>	
USB	1x USB3.0, 1x USB3.0 OTG
SERIAL	2x DB-9, RS232
LAN	1x RJ45 (10/100/1000M)
AUDIO	1x Audio Output
VIDEO	1x HDMI
OTHERS	1x SIM, 1x TF, 1x WiFi/BT4.0
<b>EXPANSION</b>	
SLOTS	1x Mini-PCle
<b>DISPLAY</b>	
DISPLAY TYPE	15.6" TFT-LCD 16:9
MAX RESOLUTION	1920 x 1080
BRIGHTNESS (cd/m <sup>2</sup> )	220
<b>TOUCHSCREEN</b>	
TOUCH SYSTEM	Projected Capacitive 10 point
<b>POWER SUPPLY</b>	
POWER INPUT	DC 12V/4A
<b>MECHANICAL</b>	
CONSTRUCTION	Aluminium Front Bezel, Aluminium chassis
MOUNTING	Panel Mount, VESA 100x100
DIMENSIONS (mm)	388.63 x 248.43 x 54.95 mm
NET WEIGHT (kg)	2.4 kg
IP RATING	IP65 compliant front bezel
<b>ENVIRONMENT</b>	
OPERATING TEMPERATURE	-20 ~ 60° C
STORAGE TEMPERATURE	-30 ~ 70° C
STORAGE HUMIDITY	95% @40°C, Non-Condensing
<b>INQUIRY CODES</b>	
LIGHT-816A	15.6" TFT, 1920x1080, RK3568, PCT, 12V/4A, 220cd/m2
<b>NOTE</b>	RAM and Storage capacity must be specified in the inquiry

