




MODEL	VLT-107A	
I/O		
VGA	1	
DVI-D / HDMI	1x Shared Port	
DP	1	
USB	1x USB type B for touch control	
AUDIO	1x (Line-in), 1x Optional Speaker	
OSD	OSD on the rear side, on board controller, extendable keypad from connector	
POWER	1x power 3-pin terminal block	
DISPLAY		
DISPLAY TYPE	7" TFT-LCD 16:10	
MAX RESOLUTION	800 x 480	
MAX COLOR	262K	
BRIGHTNESS (cd/m ²)	350	1000 (H)
VIEW ANGLE (H°/V°)	140/120	
BACKLIGHT LIFETIME (hrs)	50000	
CONTRAST	400:1	
TOUCHSCREEN		
TYPE	Resistive Zero Bezel (R) Projected Capacitive (P) Glass (G)	
INTERFACE	USB	
LIGHT TRANSMISSION	Resistive: 80 Capacitive: 90	
POWER		
POWER INPUT	9 ~ 36V DC	
POWER CONSUMPTION	4W MAX.	
MECHANICAL		
CONSTRUCTION	Aluminium die-casting chassis	
IP RATING	IP66 Compliant Front Bezel	
MOUNTING	Panel/VESA Mounting (VESA 75 x 75)	
DIMENSIONS (mm)	202 x 149 x 40	
NET WEIGHT (kg)	1.06	
ENVIRONMENT		
OPERATING TEMPERATURE	0 ~ 50° C	
STORAGE TEMPERATURE	-20 ~ 70° C	
STORAGE HUMIDITY	10 ~ 90 % non-condensing	
ORDERING		
VLT-107AP	7" TFT LCD Industrial Display Projected Capacitive Touch, 300 cd/m ²	
VLT-107AR	7" TFT LCD Industrial Display Resistive Touch Window, 300 cd/m ²	
VLT-107AG	7" TFT LCD Industrial Glass Display, 300 cd/m ²	


ALUMINIUM DISPLAY



Wide range power input



Easy Rear access to OSD



Die-casted aluminium rear



Zero bezel frontal panel

VLT-107

