


MODEL	VLT-110A
<b>I/O</b>	
VGA	1
DVI-D / HDMI	1x Shared Port
DP	1
USB	1x USB type B for touch control
AUDIO	1x (Line-in), 1x Optional Speaker
OSD	OSD on the rear side, on board controller, extendable keypad from connector
POWER	1x power 3-pin terminal block
<b>DISPLAY</b>	
DISPLAY TYPE	10" TFT-LCD 16:9
MAX RESOLUTION	1280x800
MAX COLOR	16.7M
BRIGHTNESS (cd/m <sup>2</sup> )	350
VIEW ANGLE (H°/V°)	170x170
BACKLIGHT LIFETIME (hrs)	40000
CONTRAST	500:1
<b>TOUCHSCREEN</b>	
TYPE	Resistive Zero Bezel (R)   Projected Capacitive (P)   Glass (G)
INTERFACE	USB
LIGHT TRANSMISSION	Resistive: 80   Capacitive: 90
<b>POWER</b>	
POWER INPUT	9 ~ 36V DC
POWER CONSUMPTION	5.6W MAX.
<b>MECHANICAL</b>	
CONSTRUCTION	Aluminium die-casting chassis
IP RATING	IP66 Compliant Front Bezel
MOUNTING	Panel/VESA Mounting (VESA 75 x 75)
DIMENSIONS (mm)	285 x 189 x 48.9
NET WEIGHT (kg)	1.9
<b>ENVIRONMENT</b>	
OPERATING TEMPERATURE	0 ~ 50° C
STORAGE TEMPERATURE	-20 ~ 70° C
STORAGE HUMIDITY	10 ~ 90 % non-condensing
<b>ORDERING</b>	
VLT-110AP	10.1" TFT LCD Industrial Display Projected Capacitive Touch, 350cd/m <sup>2</sup>
VLT-110AR	10.1" TFT LCD Industrial Display Resistive Touch Window, 350cd/m <sup>2</sup>
VLT-110AG	10.1" TFT LCD Industrial Glass Display, 350cd/m <sup>2</sup>


## ALUMINIUM DISPLAY



Wide range power input



Easy Rear access to OSD



Die-casted aluminium rear



Zero bezel frontal panel

