




| MODEL | VLT-112WA | |
|---------------------------------|---|---------|
| I/O | | |
| VGA | 1 | |
| DVI-D / HDMI | 1x Shared Port | |
| DP | 1 | |
| USB | 1x USB type B for touch control | |
| AUDIO | 1x (Line-in), 1x Optional Speaker | |
| OSD | OSD on the rear side, on board controller, extendable keypad from connector | |
| POWER | 1x power 3-pin terminal block | |
| DISPLAY | | |
| DISPLAY TYPE | 12.1" TFT-LCD 16:10 | |
| MAX RESOLUTION | 1280x800 | |
| MAX COLOR | 16.7M | |
| BRIGHTNESS (cd/m ²) | 600 | 1000 |
| VIEW ANGLE (H°/V°) | 170x170 | 176x176 |
| BACKLIGHT LIFETIME (hrs) | 50000 | |
| CONTRAST | 1000:1 | |
| TOUCHSCREEN | | |
| TYPE | Resistive Zero Bezel (R) Projected Capacitive (P) Glass (G) | |
| INTERFACE | USB | |
| LIGHT TRANSMISSION | Resistive: 80 Capacitive: 90 | |
| POWER | | |
| POWER INPUT | 9 ~ 36V DC | |
| POWER CONSUMPTION | 9W MAX. | |
| MECHANICAL | | |
| CONSTRUCTION | Aluminium die-casting chassis | |
| IP RATING | IP66 Compliant Front Bezel | |
| MOUNTING | Panel/VESA Mounting (VESA 100 x 100) | |
| DIMENSIONS (mm) | 328 x 227 x 57.6 | |
| NET WEIGHT (kg) | 2.7 | |
| ENVIRONMENT | | |
| OPERATING TEMPERATURE | 0 ~ 50° C | |
| STORAGE TEMPERATURE | -20 ~ 70° C | |
| STORAGE HUMIDITY | 10 ~ 90 % non-condensing | |
| ORDERING | | |
| VLT-112WAP | 12.1" 16:10 TFT LCD Industrial Display Projected Capacitive Touch, 600cd/m ² | |
| VLT-112WAR | 12.1" 16:10 TFT LCD Industrial Display Resistive Touch Window, 600cd/m ² | |
| VLT-112WAG | 12.1" 16:10 TFT LCD Industrial Glass Display, 600cd/m ² | |

ALUMINIUM DISPLAY



Wide range power input



Easy Rear access to OSD



Die-casted aluminium rear



Zero bezel frontal panel

