




ALUMINIUM DISPLAY

| MODEL | VLT-117A |
|---------------------------------|--|
| I/O | |
| VGA | 1 |
| DVI-D | 1 |
| DP | 1 |
| HDMI | 1 |
| AUDIO | 1 (Line-in) |
| OSD CONTROL MEMBRANE | OSD on the rear side, on board controller, extendable key pad from connector |
| POWER | 1x USB type-A for touch control, 1x Line-in by phone jack 1x Rs232 DB9 |
| DISPLAY | |
| DISPLAY TYPE | 17" TFT-LCD 4:3 |
| MAX RESOLUTION | 1280x1024 |
| MAX COLOR | 16.2M |
| BRIGHTNESS (cd/m ²) | 350 |
| VIEW ANGLE (H°/V°) | 170x160 |
| BACKLIGHT LIFETIME (hrs) | 30000 |
| CONTRAST | 1000:1 |
| TOUCHSCREEN | |
| TYPE | Resistive Zero Bezel (R) Projected Capacitive (P) |
| INTERFACE | USB |
| LIGHT TRANSMISSION | Resistive: 80 Capacitive: 90 |
| POWER | |
| POWER INPUT | 9 ~ 36V DC |
| POWER CONSUMPTION | 11 (P) |
| MECHANICAL | |
| CONSTRUCTION | Aluminium die-casting chassis |
| IP RATING | IP66 Compliant Front Bezel |
| MOUNTING | Panel/VESA Mounting (VESA 100 x 100) |
| DIMENSIONS (mm) | 439 x 348 x 64.8mm |
| NET WEIGHT (kg) | 6kg |
| ENVIRONMENT | |
| OPERATING TEMPERATURE | 0 ~ 50° C |
| STORAGE TEMPERATURE | -20 ~ 70° C |
| STORAGE HUMIDITY | 10 ~ 90 % non-condensing |
| ORDERING | |
| VLT-117AP | 17" TFT LCD Industrial Display Projected Capacitive Touch, 1280x1024 |
| VLT-117AR | 17" TFT LCD Industrial Display Resistive Touch Window, 1280x1024 |
| VLT-117AG | 17" TFT LCD Industrial Glass Display, 1280x1024 |



Wide range power input



Easy Rear access to OSD



Die-casted aluminium rear



Zero bezel frontal panel

