


ALUMINIUM DISPLAY



Wide range power input



Easy Rear access to OSD



Die-casted aluminium rear



Zero bezel frontal panel

MODEL	VLT-132A
I/O	
VGA	1
DVI-D	1
DP	1
HDMI	1
AUDIO	1 (Line-in)
OSD CONTROL MEMBRANE	OSD on the rear side, on board controller, extendable key pad from connector
POWER	1x USB type-A for touch control, 1x Line-in by phone jack 1x Rs232 DB9
DISPLAY	
DISPLAY TYPE	32" TFT-LCD 16:9
MAX RESOLUTION	1920x1080
MAX COLOR	16.7M
BRIGHTNESS (cd/m ²)	500
VIEW ANGLE (H°/V°)	178x178
BACKLIGHT LIFETIME (hrs)	50000
CONTRAST	3000:1
TOUCHSCREEN	
TYPE	Projected Capacitive (P)
INTERFACE	USB
LIGHT TRANSMISSION	Capacitive: 90
POWER	
POWER INPUT	90 ~ 264V
POWER CONSUMPTION	47W (P)
MECHANICAL	
CONSTRUCTION	Aluminium die-casting chassis
IP RATING	IP66 Compliant Front Bezel
MOUNTING	Panel/VESA Mounting (VESA 200 x 200)
DIMENSIONS (mm)	810 x 490 x 65 mm
NET WEIGHT (kg)	16.4kg
ENVIRONMENT	
OPERATING TEMPERATURE	0 ~ 50° C
STORAGE TEMPERATURE	-20 ~ 70° C
STORAGE HUMIDITY	10 ~ 90 % non-condensing
ORDERING	
VLT-124AP	32" FHD FPD Industrial Display Projected Capacitive Touch, 1920x1080

